

US07 Adjustable 600-1000V Secondary Cable Stripper

Introducing the new US07 Adjustable Cable Stripper that quickly and easily end strips or midspan strips cable insulation with no conductor damage on #8 to 1000 kcmil secondary cables. The tool utilizes a size adjustment clamping system to swiftly adjust and lock onto the insulation. Its compact, low friction, thermoplastic, impact-resistant polymer v-jaw and body provides a stable and precise clamping platform in any space.

Features

- Equipped with safe, recessed blade to prevent potential injury & blade damage
- Quickly adjusts to suit THHN, XHHW & USE secondary cables with 0.3" to 1.375" (7.6 mm to 35 mm) cable diameters, eliminating the need for bushings
- Easily adjusts with detent actuated knob & fine adjustment knob to match insulation thickness for fast stripping without conductor damage
- Features a replaceable, machined & ground tool steel blade
- Combines the end & mid-span strip performance of the UtilityTool[®] WS 71 & WS 72 with added features, stability & cable sizes
- Durable bronze bushings provides longevity

Compatibility

| PART # | CABLE DIAMETER OVER INSULATION | JACKET TYPES | INSULATION THICKNESS | REPLACEMENT BLADE PART # |
|-----------|--------------------------------|---------------------|----------------------|-----------------------------|
| US07-7000 | 0.3" to 1.375" (7.6 to 35 mm) | THHN XHHW USE | 45 to 125 mils | US07-7500 |



Adjustable to suit #8 to 1000 kcmil secondary cables with various insulation thicknesses.



Ergonomic comfort grip & rotating handle increases leverage.



Recessed steel blade assures safety & is easily replaced.



Unique, low-friction V-jaw provides precise & accurate clamping.









Make Cable Preparation Easier

With Additional Ripley[®] Products



RCC

Rachet Cable Cutter

- Easily cuts through copper, aluminum, solid & stranded conductors
- Not suitable for steel or ACSR cable
- Quick-release thumb lever enables user to halt operation & remove if necessary

| MODEL | PART # | CABLE SIZE Ø |
|-------|---------|-------------------------------|
| RCC | 34925-2 | Up to 1.75" Up to 44.45 mm |



SCS

Semi-Con Scoring Tool

- Provides accurate semi-con scoring; capable of longitudinal & spiral cuts
- Precise & easily adjustable blade depths from 0" to 0.16" (0 to 4 mm) in increments of 0.002" (0.05 mm)
- Compact design for easy use & storage

| MODEL | PART # | SCALE | CABLE SIZE Ø |
|-------|--------|-----------|----------------|
| SCS | 43630 | Customary | 0.31" to 1.77" |
| SCS | 43625 | Metric | 8 to 45 mm |



RFNP Series

Flat Nose Pliers

- Comfortable, ergonomic & slip-free dual-compound thermoplastic grips
- 10⁶ to 10⁹ ohms/sq surface resistance per IEC 61340-5-4 for ESD workstations
- Drop-forged, hardened & tempered steel alloy for strength & longevity

| MODEL | PART # | ΤΥΡΕ | LENGTH |
|--------|--------|------------|---------------|
| RFNP-S | 46475 | Short Nose | 5.1" (130 mm) |
| RFNP | 46474 | Long Nose | 5.7" (145 mm) |



QC-2

Quick Cable Clamp

- Easy-to-use, heavy duty aluminum clamp quickly attaches to stop jacket stripping operations
- Convenient ratchet allows for relocation of handle position

| MODEL | PART # | CABLE SIZE Ø |
|-------|--------|---------------------------------|
| QC-2 | 43970 | 0.5" to 2.5" 12.7 to 63.5 mm |



WS 76

Semi-Con Shaving Tool

- Easily transitions between spiral shaving to cutting bevelled edges at 20°
- Accurately removes semi-con jacket within 0.984" (25 mm) & semi-con shield within 0.275" (7 mm)
- Precision blade adjusts in 0.004" (0.1 mm) increments

| MODEL | PART # | CABLE SIZE Ø |
|-------|--------|-------------------------------|
| WS 76 | 43580 | 0.71" to 2.36" 18 to 60 mm |

US10 Series

15-35kV URD Chamfering Tool

- Size adjustment clamping system quickly & easily adjusts, then locks onto the insulation
- Chamfers 15 to 35 kV cable to 30° bevel, 0.15" (3.91 mm) in length
- Compact & ergonomic design with recessed blades to prevent injury
- Easily adjusts to accommodate XLPE, EPR & other cable insulations

| MODEL | PART # | CABLE SIZE Ø |
|-------|-----------|-------------------------------|
| US10 | US10-7000 | 0.55" to 2.36" 14 to 60 mm |

LIT-UT-0008 REV. A



