



P81001 Clamp-on Ground Resistance Tester

EARTH GROUND RESISTANCE TESTERS



PRODUCT FEATURES

- Auto-ranging ground resistance measurements from 0.01 Ω hm to 1000 Ω hm with 0.01 Ω hm resolution
- AC leakage current range of 10mA to 30.00A with 50 μ A resolution
- 1.25" maximum conductor O.D.
- Configurable alarm value for resistance and current to support your measurement
- Ergonomic mold with complete slip-proof rubber coating
- Simplifies ground resistance measurements on multiple point ground systems
- Verification resistor included to confirm accuracy of meter
- Data logging with 99 data points
- Complete with heavy-duty case

Want to know more about our Utility Pro Products line or need a quote?

www.sncmfg.com | info@sncmfg.com

Transforming tomorrow.



P81001 Clamp-on Ground Resistance Tester



GENERAL CHARACTERISTICS

POWER

AA1.5Vx4

PRODUCT SIZE

11.22" x 3.54" x 2.36"
(285 x 90 x 60 mm)

PRODUCT NET WEIGHT

2.9 lbs. (1320g)
(including battery)

STANDARD INDIVIDUAL PACKING



Carry Case

STANDARD QUANTITY PER CARTON

1 pc.

MEASUREMENT OF STANDARD CARTON

25.39" x 14.17" x 10.83"
(645 x 360 x 276mm)
0.064

GROSS WEIGHT OF STANDARD CARTON

4 lbs. (1.81kgs)

SPECIFICATIONS

	Range	Resolution	Precision
Earth Ground Resistance	0.01Ω~0.99Ω	0.01Ω	±1%+0.01Ω
	1.0Ω~49.9Ω	0.1Ω	±1.5%+0.1Ω
	50.0Ω~99.5Ω	0.5Ω	±2%+0.5Ω
	100Ω~199Ω	1Ω	±3%+1Ω
	200Ω~395Ω	5Ω	±6%+5Ω
	400Ω~590Ω	10Ω	±10%+10Ω
	600Ω~1000Ω	20Ω	±20%+20Ω
Min. Resolution	0.01Ω	1,000 - 5,000	
Configurable alarm value of resistance	0~199Ω	50 - 750	
Leakage current	0~80mA	50μA	±2.5%+1mA
	80mA~650mA	0.5mA	±2.5%+2mA
	650mA~4A	5mA	±2.5%+10mA
	4A~30A	10mA	±2.5%+20mA
Min. Resolution	50μA		
Measurement of leakage current	46~65 Hz, RMS		
Configurable alarm value of current	0~499mA		
Memory	99 sets		
Conductor Size	1.26" - 2.17" (32 - 55 mm)		
Working Temperature	14° - 131°F (-10°C~55°C)		
Working Humidity	10%~80%		
LCD Size	1.12 x 1.85" (28.5 x 47 mm)		

Learn more about how our custom solutions can transform tomorrow's products.



Connect on social:

www.sncmfg.com | 800-558-3325 | info@sncmfg.com

T0619

